

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number
WO 2005/085406 A1

(51) International Patent Classification⁷: C11D 3/22, 3/37

(21) International Application Number:
PCT/GB2005/000428

(22) International Filing Date: 8 February 2005 (08.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0404326.1 27 February 2004 (27.02.2004) GB

(71) Applicant (for all designated States except US):
RECKITT BENCKISER (UK) LIMITED [GB/GB];
103-105 Bath Road, Slough, Berkshire SL1 3UH (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **COBB, Victoria, Heather** [GB/GB]; Reckitt Benckiser Corporate Services Limited, Dansom Lane, Hull HU8 7DS (GB). **DUDDINGTON, Andrea** [GB/GB]; Reckitt Benckiser Corporate Services Limited, Dansom Lane, Hull HU8 7DS (GB). **ILIFFE, Coreen, Jane** [GB/GB]; Reckitt Benckiser Corporate Services Limited, Dansom Lane, Hull HU8 7DS (GB). **JOLLIFFE, Ian, Gordon** [GB/GB]; Reckitt Benckiser Healthcare (UK) Limited, Dansom Lane, Hull HU8 7DS (GB).

(74) Agents: **INSTONE, Terry** et al.; Intellectual Property Department - Patents Group, Reckitt Benckiser Plc, Dansom Lane, Hull HU8 7DS (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF TREATMENT OF A SURFACE

(57) Abstract: Kits, applicators and methods for treatment of a surface involve sequential application to a surface of a hydrogel precursor and a crosslinking component to form a removable hydrogel patch on the surface followed by removal of the patch. The method is suitable for removal of a stain from a surface .



WO 2005/085406 A1

METHOD OF TREATMENT OF A SURFACE

The present invention relates to a method for the treatment of a surface, particularly a textile surface, and more particularly to a method for the treatment of a surface such that a stain is removed, or at least partially removed. The present invention also relates to products for use in such methods.

10 It is well-known to treat textiles such as clothing, carpets, mats, upholstery, fabrics, wall-coverings, and the like in various ways. For instance, it is possible to treat textiles to impart a fragrance thereto, to condition them (for example, by the use of anti-static agents, and the like), or to cleanse them (by the use of powder or liquid detergent compositions, and the like).

Conventionally, in order to perform the task of washing textiles, that is, in order to remove common stains and the like, some water and a washing machine is required to complete the washing task. Moreover, the task can take several hours to complete, including the drying process. In addition, this conventional process will wash the whole garment or article, and in the case of a spot stain, this is clearly not necessarily required. In effect, the conventional washing/drying process is both time-consuming and wasteful of resources if all that is required is treatment of a spot stain. Conventional dry cleaning processes have similar drawbacks.

30

A further disadvantage in using conventional washing processes when treating spot stains is that it is not always possible or convenient to treat the spot stain

immediately, for instance if the required conventional washing equipment is not to hand. It is also known that in general, the quicker a stain is treated, such as a spot stain, the better the chance of successful removal.

5 Moreover, it is often most convenient to deal with a spot stain as soon as it occurs such that one can perhaps avoid the need of washing the textile at all using conventional processes, or the spot stain can be removed or at least partially removed, such that effect of any unsightly stain

10 is reduced to a level that allows the reduced stain to be tolerated, perhaps until conventional washing processes, or dry cleaning processes, can be employed.

Therefore, there is the need to provide convenient stain

15 removing or partially removing (i.e. stain reducing) patches which seek to alleviate the above-mentioned drawbacks of conventional washing processes, and/or provide convenient methods of stain removal/reduction, such as stain removal/reduction without the need for a

20 full conventional washing process. Moreover, there is the need to provide stain removing/reducing patches which improve the effectiveness of the conventional washing or dry cleaning processes.

25 WO-A-02/102957 (to Reckitt Benckiser (UK) Limited) discloses textile treatment compositions comprising a patch with a water impervious backing made of a polymer sheet to which is attached a hydrogel containing a surfactant treatment fluid.

30 Nevertheless, there remains the need for alternative and/or improved methods for the treatment of surfaces, particularly textile surfaces, for the removal/reduction

of stains, both in terms of user convenience and stain removal/reduction ability, and for alternative and/or improved surface, particularly textile surface, treatment compositions.

5

Therefore, in a first aspect, the present invention provides a method for the treatment of a surface comprising the sequential application to the surface of a hydrogel-precursor component and a crosslinking component,
10 in either order, to form a removable hydrogel patch on said surface, and the removal of the patch once the removable hydrogel patch has formed or substantially formed thereon.

15 Thus, in the method of the invention, the hydrogel-precursor and crosslinking components are kept separate from each other until they are sequentially applied to the surface.

20 By "sequential", we mean that the second (and further, if present) component is applied to the surface after the first (or previous) component has been applied, more preferably with a time gap between such applications, as described hereinafter.

25

Preferably, the method is such that it can conveniently be carried out in circumstances where there is no availability of conventional washing processes, or where such conventional processes would be inconvenient, for
30 instance where the user wishes to treat a spot stain immediately, for instance as and when staining occurs. In such cases, it may not be necessary to clean the whole

surface and the present method enables just the area of the surface stained to be treated.

Moreover, although the removal of the removable patch is
5 generally performed manually by the user, for example by peeling, it is also possible for the removable patch, once formed, to be removed as part of the conventional washing or dry cleaning process, such as in a textile washing machine. In such cases, the removable patch comprises a
10 water-soluble or dispersible polymer which dissolves or disperses into a wash liquor. Thus, one benefit of the method of the invention is that it is possible for the user to control the formation of the removable patch as soon as possible after the staining has occurred and the
15 conventional washing/dry cleaning process can then be carried out at a convenient time thereafter. Conventional wash pre-treatments essentially require the washing/dry cleaning process to follow almost immediately after application of the pre-treatment formulation, i.e. whilst
20 the pre-treatment is still wet. Hence, the present method enables the treating effect of the removable patch to be started as soon as practical after staining, with the washing/dry cleaning process following at a convenient time thereafter.

25

The hydrogel-precursor and crosslinking components are components comprising respectively a hydrogel-precursor and a crosslinker capable of crosslinking the hydrogel-precursor to form a hydrogel patch. Preferably the two
30 components are both liquids. By liquid it is meant that they have a viscosity of 100,000mPa.s or less at a shear rate of 1s^{-1} measured at 25°C .

Suitably, the method of the invention enables the user to more precisely determine the onset of the formation of the patch, by the sequential addition of the two components, particularly as the two components are preferably such
5 that patch formation requires the presence of both or the at least two components. As such, the user can either speed up the onset of patch formation by adding the at least two components in fairly quick succession, and thus quicken the overall treatment method, or the user can
10 delay the onset of the patch formation by leaving a longer time delay before adding the second component, and thus slow down the overall treatment method, giving further time for the still liquid first component to penetrate into the textile. As the removal/reduction of a stain
15 will be enhanced by at least part of the stain passing into the liquid components and then being "locked" into the patch as it forms, delaying the onset of patch formation can be advantageous.

20 Preferably, by "treatment" we mean cleaning, more preferably stain removal or reduction.

By "removable patch" we mean a patch that has sufficient solid or gel-like characteristics that it is peelable or
25 otherwise substantially removable by the user without the user requiring any specialist techniques or aids, or which is removed by conventional washing or dry cleaning processes after becoming solid or substantially solid or gel-like.

30

By "surface", we include both hard and soft surfaces. By "hard surface", we include ceramics, glass, stone, plastics, marble, metal and/or wood surfaces, such as, in

the household environment for example, bathroom and kitchen hard surfaces such as sinks, bowls, toilets, panels, tiles, worktops, dishes, and the like. Hard surfaces are non-porous to water, by which it is meant
5 that a hard surface, on contact with water for 5 minutes, takes up less than 5 mg of water per cm².

By "soft surface", we include textiles, clothing, carpets, curtains, upholstery, textile or fabric covered articles,
10 and the like. Soft surfaces are porous to water, by which it is meant that a hard surface, on contact with water for 5 minutes, takes up 5 mg or of water per cm².

Thus, there is provided a method of spot stain
15 removal/reduction, which is convenient, practical, can be performed *in situ* (i.e. by the user immediately after the stain is noted), available wherever the user is situated, and employable without necessarily requiring conventional washing means, or a method which improves the
20 effectiveness of the eventual washing process. In essence, the user is in control of the formation of the patch and can thus conveniently apply removable-patch forming components at his convenience. A yet further advantage is that the user is able to visibly see the
25 stain passing into the removable patch as it forms and once removed, the patch may show some colouration from the stain, confirming to the user the effectiveness of the method. A still yet further advantage of the present invention is that the user can control the onset of patch
30 formation by the timing of the sequential addition of the components. A yet further advantage is that no pre-mixing of the components is required.

The crosslinking component cross-links the hydrogel-precursor polymeric material of the hydrogel-precursor component as part of the patch-forming process, leading to the formation of a hydrogel patch. Therefore, a requirement for this crosslinking component is that it comprises a species capable of cross-linking the polymer material of the other component as part of the patch-forming process.

10

By the term "hydrogel" as used herein it is meant a natural or synthetic polymeric material which possesses the ability to swell in water. The hydrogel may be water-insoluble or water-soluble; preferably it has a solubility in water of less than 1 g/dm³. By "hydrogel-precursor" is meant a material which can be cross-linked in order to form a hydrogel. Natural hydrogel precursors are suitable for the invention, such as alginates and other polysaccharides with free carboxylic acid groups.

20

Suitably, the hydrogel-precursor is a hydrophilic homopolymer or copolymer of acrylic or methacrylic acid, or a salt thereof; or a carboxylated cellulose derivative. The polymer, once formed into a hydrogel, is cross-linked to a relatively low degree and but for the cross-linking would be essentially water-soluble.

The polymer may include in its structure a polysaccharide such as starch, for example in a graft copolymer.

30

Where the hydrogel-precursor comprises free carboxylate groups as described above, the crosslinking component suitably comprises metal M²⁺ ions (where M is a Group IIA

element or any other metallic element capable of exhibiting a +2 oxidation state), more preferably wherein M is a Group IIA element, even more preferably Ca^{2+} ions, i.e. this liquid component comprises an M^{2+} salt, e.g. a calcium salt. Yet more preferably, this liquid component comprises Ca^{2+} ions in the form of calcium chloride.

In another embodiment, the hydrogel precursor may be carrageenan, preferably iota-carrageenan, or pectin. For these materials, calcium ions are suitable crosslinking agents. Another suitable hydrogel precursor is chitosan, which is soluble in acidic or protonated form, and gels in the presence of alkali. If the hydrogel-precursor component comprises chitosan, the crosslinking component should comprise an alkali, preferably sodium hydroxide.

More preferably, the hydrogel-precursor comprises alginic acid or an alginate, where an alginate is a salt of alginic acid, even more preferably, a sodium alginate. Hereinafter, the term "alginate" is used to refer to either alginic acid or a water-soluble salt thereof, such as a sodium salt.

Alginic acid or alginates may be found in and isolated from various organisms, in particular from algae belonging to the order Phaeophyceae and soil bacteria such as *Azotobacter vinelandii* and *Azotobacter crococcum* and from several strains of *Pseudomonas* bacteria. Common algal sources of alginates include *Laminaria digitata*, *Ecklonia maxima*, *Macrocystis pyrifera*, *Lessonia nigrescens*, *Ascophyllum nodosum*, *Laminaria japonica*, *Durvillea antarctica*, *Durvillea potatorum* and, especially, *Laminaria hyperborea*.

Alginic acid is a linear hetero-polysaccharide comprising units of β -D-mannuronic acid and α -L-guluronic acid. Alginic acid may comprise homopolymeric sequences of mannuronic acid, homopolymeric sequences of guluronic acid, and mixed sequences of mannuronic acid and guluronic acid units.

Salts of alginic acid used in the method of the present invention may include alkali metal salts, for example sodium and potassium salts, and ammonium and alkanolamine salts. Alkali metal salts are of particular interest.

The terms "algins" or "alginates" as used herein include alginic acid and salts of alginic acid, irrespective of the relative proportion of mannuronic and guluronic units, and is intended to include glycolated or alkoxyated derivatives, especially those derivatised with propylene glycol. However, preferred compounds are not alkoxyated or glycolated. Guluronic acid-rich alginic acid and guluronic acid-rich salts of alginic acid are of particular interest. Preferred compounds have at least 50%, more preferably 55-99%, most preferably 60-80% of guluronic units (by weight of the polymer), the balance being mannuronic units. For guidance on production of algins very high in guluronic units the reader is referred to WO 98/51710.

The crosslinking and hydrogel-precursor components may be applied sequentially in either order: crosslinking component first or hydrogel-precursor component first. However it is preferred that the first component applied to the surface is the crosslinking component and the

second liquid component to be added is the hydrogel-precursor component.

In the above-mentioned embodiments, the method of the invention results in the formation of a gel-like patch which, after a suitable time period, can be removed by the user from the surface to which the components have been sequentially applied. Clearly, the easier the patch is to remove from the surface, the more user-friendly and effective will be the method of the invention. It has been found that sequential addition of a third component, i.e. a treatment method comprising the steps of the sequential addition of three liquid components to form a removable patch, and the removal of the patch once the said removable patch has formed or substantially formed, is preferred when the third component acts as a hardener or setting agent and as such, decreases the time for the patch to form or to substantially form. In this preferred embodiment, the first liquid component is preferably the crosslinking component and is also found to be a preferred third component. Hence, in this preferred embodiment, the sequential addition of components is as follows: first component, crosslinking component; second component, hydrogel-precursor component, as hereinbefore defined; third component as first component (as hereinbefore defined).

Even more preferably, the first component comprises CaCl_2 , the second component comprises an alginate, preferably a sodium alginate, the third component comprises CaCl_2 .

However, although a decrease in the time taken to form or substantially form the removable patch can in some

instances be preferred, particularly from the point of view of convenience and hence user-compliance, in other instances where the stain removal is taking place whilst the patch forms, an increase in the time taken for the patch to form can be an advantage. In effect, there is a balance between the shorter times preferred for user-friendliness and convenience, and the slightly longer times preferred to enable more of the stain to be taken out of the surface (by wicking, capillary action, or diffusion into the components, as the removable patch forms from the liquid components). Preferably, a removable patch is formed or substantially formed between 30 secs and 15 mins after the final component is applied, more preferably between 45 secs and 12 mins after the final component is applied, most preferably between 1 min and 10 mins after the final component is applied.

Preferably, the cross-linking component comprises M^{2+} ions, preferably Ca^{2+} ions in the range 0.03 to 5 wt% of the overall weight of this component, more preferably in the range 0.05 to 4 wt%, even more preferably in the range 0.1 to 3 wt%, most preferably in the range 0.2 to 2 wt%.

When the metal ion is provided by calcium chloride, the preferred weight percentage expressed as weight percent of $CaCl_2 \cdot 2H_2O$ in the crosslinking component is 0.1 to 20 wt% of the overall weight of this component, more preferably 0.6 to 19 wt%, even more preferably 0.8 to 17 wt%, most preferably 1 to 16 wt%.

Preferably, the hydrogel-precursor component, more preferably comprising an alginate, comprises hydrogel-precursor in the range 0.1 to 10 wt% compared to the

overall weight of that component, more preferably in the range 0.25 to 5 wt%, most preferably 0.4 to 4 wt%, for example 0.5 wt% to 3 wt%. More preferably, when alginate is used, the alginate should have a G-block content of at least 15% of the total polymer weight, even more preferably at least 25%, most preferably at least 35%, as this is found to increase the integrity of the patch thus formed and hence the ease with which the removable patch thus formed can be removed. More preferably the alginates have at least 50%, even more preferably 55-99%, most preferably 60-80% of guluronic units (by weight), the balance being mannuronic units.

Without wishing to be bound by theory, alginates are, as noted hereinbefore, comprised of mannuronate and guluronate monomers and in order to form a gel, and thus a usable patch in the method of the present invention, the alginate should contain a sufficient level of guluronate monomers in a block to react with the metal cations, such as divalent ions, from the other component(s) to form a gel. It is believed that the divalent ions especially, essentially "fit" into the guluronate block structure in suitable alginates.

Suitable alginates for use in the method of the present invention include those in the Protanal™ range, LF20™, GP6650™, and XP3499™ (all available from FMC BioPolymer of Philadelphia, PA 19103, USA). Protanal™ LF20™ is preferred and is a sodium alginate available from FMC BioPolymer. A 1 wt% aqueous solution thereof at ambient temperature of 25°C has a viscosity of 155 to 255 mPa.s at a shear rate of 1 s⁻¹ and a pH of 6.0 to 8.0.

Preferably, all components used in the method of the present invention are liquid solutions, more preferably aqueous solutions (i.e. free-flowing aqueous solutions).

5 In further embodiments of the invention further agents or moieties can be in one, more, or all of the components of the method of the invention, as described below, which may improve still further the treatment ability of the method of the invention.

10

For the avoidance of doubt, any one or more of these agents can be added to the components as set out hereinafter, in any mutually compatible manner.

15 Hence, a yet further advantage of the method of the present invention is that because the at least two components are kept separate as and until the user wishes to form the patch, it is possible for mutually incompatible or antagonistic further ingredients or agents
20 to also be effectively kept apart, as and until the removable patch is to be formed.

Silicones

25 It is preferred if at least one of the two components of the method of the invention comprises a silicone oil, preferably a cyclic or linear polydimethylsiloxane preferably having a viscosity at 25°C and a shear rate of 1 sec⁻¹ of from 10 to 10,000 mPa.s.

30

Such silicone oil is suitably in the form of emulsified droplets, preferably in the hydrogel-precursor component of the invention. A suitable level is from 0.1 to 2%,

preferably from 0.5 to 1.5% by weight of the hydrogel patch formed in the method. Suitable surfactants for use in emulsification may be as described below. Alternatively, a silicone-based surfactant may be used.

5

The advantage of the presence of the silicone oil in the components used in the method of the invention is that it provides improved peelability for the hydrogel patch.

10 Anti-Limescale Agents

Examples of anti-limescale agents include acids, particularly organic acids (e.g. citric acid), and anti-nucleating polymers, such as polyacrylates. Other
15 relevant acids that may be present include glycolic and sulphamic acids. Preferably, the amount of acid present for limescale removal is sufficient to provide an overall pH of the patch of 1-7, more preferably 2-7, most preferably 3-6.

20

Bleach

Peroxygen bleaching agents are preferred. Suitable peroxygen bleaching compounds include sodium carbonate
25 peroxyhydrate and equivalent "percarbonate" bleaches, sodium pyrophosphate peroxyhydrate, urea peroxyhydrate, and sodium peroxide. Persulfate bleach (e.g. OXONE, manufactured commercially by DuPont) can also be used. Perestane or PAP are also suitable bleaches for use with
30 the invention.

Bleach activators can also be present. Bleach activators lead to the in situ production in aqueous solution of the peroxy acid corresponding to the bleach activator. Various nonlimiting examples of activators are disclosed
5 in US Patent 4,915,854, issued April 10, 1990 to Mao et al, and US Patent 4,412,934. The nonanoyloxybenzene sulfonate (NOBS) and tetraacetylene diamine (TAED) activators are typical and are preferred, and mixtures thereof can also be used. See also US 4,634,551 for other
10 typical bleaches and activators useful herein.

The bleach system if present, may be in the cross-linking component.

15 More preferably, the bleach system is contained in the component containing the hydrogel-precursor. It has been found that this gives improved stain removal from soft surfaces compared to having the bleach in with the other component.

20

The bleach is present at a level in the range 0 to 8 wt%, more preferably 1 to 7 wt%, most preferably in the range 2 to 6 wt%, of the component in which it is situated.

25

In embodiments of the invention where a peroxide or peroxide generator is used as a bleach system, it is preferred if the peroxide or peroxide generator is present in the hydrogel-precursor component at a pH from 4 to 6,
30 preferably 4.5 to 5.5. At lower pH the precursor may be unstable. At higher pH the peroxide may dissociate on storage.

In such embodiments, it is preferred if the pH of the other, cross-linking component is 8 to 10, preferably 8.5 to 9.5. This helps to increase the effectiveness of the peroxide for bleaching when the components are mixed. If
5 the pH of the metal ion-containing component is too high, the ions may precipitate from solution, especially where Ca^{2+} ions are present.

Enzymes

10

Enzymes can be included in the components herein for a wide variety of fabric laundering purposes, including removal of protein-based, carbohydrate-based, or triglyceride-based stains, for example, and for the
15 prevention of dye transfer, and for fabric restoration. The enzymes to be incorporated include proteases, amylases, lipases, cellulases, and peroxidases, as well as mixtures thereof. Other types of enzymes may also be included. They may be of any suitable origin, such as
20 vegetable, animal, bacterial, fungal and yeast origin. However, their choice is governed by several factors such as pH-activity and/or stability optima, thermostability, stability versus active detergents, builders and so on. In this respect bacterial or fungal enzymes are preferred,
25 such as bacterial amylases and proteases, and fungal cellulases.

Preferably, enzymes if present, are in any component, at a level in the range 0.001 to 5 wt%, more preferably 0.01 to
30 1 wt%, of the component.

Solvent

Solvents, particularly organic solvents, may be present in any of the components. More preferably, organic solvents, such as glycol ethers, C₁-C₁₀ alcohols, C₁-C₁₀ hydrocarbons or halohydrocarbons, carbonyl-based solvents such as acetone, and the like, are present, preferably in the component(s) comprising M²⁺ ions. The organic solvent, if present, should preferably be included in an amount from 5 to 50 wt% of the component. The overall levels of organic solvents should be within the VOC limits of cleaning products and preferably, the maximum level of organic solvent in each component is 8 wt%, more preferably, up to 6 wt%, most preferably up to 4 wt%.

Surfactant

15

Non-limiting examples of surfactants useful herein comprise an anionic such as sulfonates, sulphates and ether sulphates or/and a nonionic such as a ethoxy or propoxylated alkyl, fatty acid or alcohol. These include the conventional C₁₁-C₁₈ alkyl benzene sulfonates ("LAS") and primary, branched-chain and random C₁₀-C₂₀ alkyl sulfates ("AS"), the C₁₀-C₁₈ secondary (2,3) alkyl sulfates of the formula CH₃(CH₂)_x(CHOSO₃-M⁺)CH₃ and CH₃(CH₂)_y(CHOSO₃-M⁺)CH₂CH₃ where x and (y + 1) are integers of at least about 7, preferably at least about 9, and M is a water-solubilising cation, especially sodium, unsaturated sulfates such as oleyl sulfate, the C₁₀-C₁₈ alkyl alkoxy sulfates ("AExS"; especially EO 1-7 ethoxy sulfates). C₁₀-C₁₈ alkyl alkoxy carboxylates (especially the EO₁₋₅ ethoxycarboxylates), the C₁₀-18 glycerol ethers, the C₁₀-C₁₈ alkylpolyglycosides and their corresponding sulfated polyglycosides, and C₁₂-C₁₈ alpha-sulfonated fatty acid esters. If desired, the conventional nonionic

and amphoteric surfactants such as the C12-C18 alkyl ethoxylates ("AE") including the so-called narrow peaked alkyl ethoxylates and C6-C12 alkyl phenol alkoxylates (especially ethoxylates and mixed ethoxy/propoxy), C12-
5 C18 betaines and sulfobetaines ("sultaines"), C10-C18 amine oxides, and the like, can also be included in the overall compositions. The C10-C18 N-alkyl polyhydroxy fatty acid amides can also be used. Typical examples include the C12-C18 N-methylglucamides. See WO 92/06154.
10 Other sugar-derived surfactants include the N-alkoxy polyhydroxy fatty acid amides, such as C10-C18 N-(3-methoxypropyl) glucamide. Mixtures of anionic and nonionic surfactants are especially useful. Other conventional useful anionic, amphoteric, nonionic or
15 cationic surfactants are listed in standard texts.

Preferably, the surfactant is sodium lauroyl sarcosinate, available in 30% form as SURFAC SL30F™ (from Surfachem Plc, Leeds LS1 4LT, UK). More preferably, Sodium lauryl
20 sulphate is employed as the surfactant.

Preferably, surfactant(s) if present, is/are in the hydrogel-precursor component, at a level in the range 0.01 to 50 wt%, more preferably 0.05 to 20 wt%, most preferably 0.1 to 10 wt%, for example 4 wt%, of the component.

25

Anionic surfactants are preferred over nonionic or zwitterionic surfactants, in that they give improved peelability of the formed hydrogel patch.

30 Preferably, at least one of the components used in the method of the invention further includes one or more of the following: a bleach (with or without a bleach activator), an enzyme or enzyme system (including any

necessary stabilisers) and at least one surfactant, more preferably at least one surfactant. In this particular embodiment, i.e. when the method is essentially an enhanced cleaning method (due to the presence of the bleach/enzyme/surfactant agent(s)), any or all of the components may further comprise fragrances. Preferred fragrances which can be included in the components herein include but are not limited to those selected from the group consisting of aromatic and aliphatic esters, for example those esters having molecular weights of from 100 to 300, preferably 130 to 250; aliphatic and aromatic alcohols, for example those having molecular weights of from 75 to 250, preferably 90 to 240; aliphatic ketones, for example those having molecular weights of from 100 to 300, preferably 150 to 260; aromatic ketones, for example those having molecular weights of from 100 to 300, preferably 150 to 270; aromatic and aliphatic lactones, for example those having molecular weights of from 100 to 350, preferably 130 to 290; aliphatic aldehydes, for example those having molecular weights of from 100 to 250, preferably 140 to 200; aromatic aldehydes, for example those having molecular weights from 50 to 250, preferably 90 to 230; aliphatic and aromatic ethers, for example those having molecular weights of from 100 to 300, preferably 150 to 270; and condensation products of aldehydes and amines, for example those having molecular weights of from 100 to 400, preferably 180 to 320.

Preferably, if present in the components used in the enhanced cleaning methods of this embodiment of the invention, fragrance is in either component at a level in the range of 0.1 to 5 wt%, more preferably 0.2 to 4 wt%,

most preferably 0.5 to 3 wt%, of the weight of the component.

More preferably, at least one of the components used in
5 the method of the present invention comprises at least one surfactant.

Sequestrant

10 Sequestrants, such as Dequest 2066™ (available from Solutia Inc., St Louis 6366-6760, USA), EDTA, and Dissolvine EDG™ (available from Akzo Nobel, Gillingham, ME7 1RL, UK), aid in stain removal and hence are preferably present in one or more of the components of the
15 method of the present invention, more preferably in the hydrogel-containing component.

The overall level of sequestrant present should be within permitted phosphorus regulations, if relevant. Hence, the
20 upper limit to be used is specific to the particular sequestrant. Thus, for Dequest™ 2066, the amount present is preferably up to 1.5 wt%, more preferably up to 1 wt%, most preferably up to 0.8 wt%, for example 0.8 wt% of the component. Where permitted phosphorus regulations are not
25 relevant, the sequestrant may be present up to 20 wt%, more preferably 15 wt%, of the component. Preferably, the sequestrant is present in any hydrogel-precursor component.

30 Particularly preferred sequestrants for use with the invention are iminodisuccinic acid or its salts and/or DTPA (diethylene triamine pentaacetic acid).

Glycerol

Glycerol is found to improve the integrity and hence the peelability and thus removability of the patch formed
5 using the method of the present invention, particularly when the glycerol is in the hydrogel-containing component.

Thus, although glycerol is an optional presence in any hydrogel-containing components of the method of the
10 present invention at between 0 and 50 wt%, when present it is preferably found at 2 to 25 wt%, more preferably 4 to 20 wt%, most preferably 6 to 15 wt%, of that component.

The components of the invention are made up to 100 wt% by
15 water, preferably de-ionised water, at levels of 5 to 99 wt% water.

Any or all of the components may further comprise additional cleaning agents, such as monoethanolamine and
20 triethanolamine, at levels in the range 5-20 wt%, more preferably 5-15 wt%, most preferably 5 to 10 wt%, of the respective component.

Any or all of the components may further comprise
25 additional ingredients, such as antimicrobials (e.g. quaternary ammonium compounds, triclosan, and other phenolic agents such as para-chloro meta xylenol (PCMX), citric acid, lactic acid) and if present, are preferably present in the range of 0.01 to 5 wt% of the component,
30 more preferably in the range 0.02 to 3 wt%, e.g. at 1 wt% (especially for triclosan); preservatives, e.g. methylparaben, ethylparaben, propylparaben, or mixtures thereof (if present, preferably present in the range of

0.01 to 0.5 wt% of the component, more preferably in the range 0.01 to 0.2 wt%); or film formers such as polyvinyl alcohol (preferably present in the range of 0-50 wt% of the component where present), polyvinyl alcohol/vinyl acetate copolymers (preferably present in the range of 0-50 wt% of the component where present), and polyvinylpyrrolidone/vinyl acetate copolymers (preferably present in the range of 0-50 wt% of the component where present).

10

Dyes can also be added to any component to make a coloured patch.

Preferably, in the method of the present invention the user applies a first component to cover all or substantially all of the stain, and then, preferably within 120 seconds, more preferably within 90 seconds, even more preferably within 60 seconds, most preferably within 30 seconds, e.g. as soon as reasonably practical thereafter, applies a second component to cover all or substantially all of the first component, wherein these components are the components described hereinbefore, i.e. preferably a hydrogel-precursor component and a crosslinking component comprising M^{2+} ions. Where a third component is to be added, this is applied to cover all or substantially all of the second component, within similar time periods to those noted above, with the overall application of all components being preferably within 180 secs, more preferably within 120 secs, most preferably within 90 secs.

The components are then left until a removable patch has formed or substantially formed, which can then be removed

by the user. Typically the patch takes between 10 secs and 10 mins after application of the final component, and may in certain embodiments, particularly when surfactant is present, be indicated by the formation of a white
5 colour as the patch forms or substantially forms. Thus, preferably, the patch is removed at least 10 secs after application of the final component, more preferably at least 1 min after application of the final component, even more preferably at least 2 mins after application of the
10 final component, yet even more preferably at least 5 mins after application of the final component, most preferably at least 10 mins after application of the final component.

The method of the present aspect of the invention may
15 remove or substantially remove many if not all common stains found on textiles and the like, e.g. oxidisable, such as coffee, tea and wine stains, proteinaceous stains, together with 'greasy' stains such as those produced by lipstick and the like, grass stains etc.

20 Additional, and optional, method steps include the following:

- i) applying force to the patch as it is forming;
- 25 ii) removing said force once applied;
- iii) rubbing the patch as it is forming;
- iv) immersing the surface into a wash liquid.

However, the nature of the patch formed by the method of
30 the invention is such that all of the above steps are optional. Therefore a yet further advantage of the method is its simplicity and hence the increased likelihood of

user compliance and thus effective treatment of the surface.

5

According to a further aspect of the present invention there is provided a removable patch comprising a hydrogel-precursor component, and a crosslinking component, both as described hereinbefore, and wherein said patch is
10 obtainable by the method described hereinbefore.

According to a yet further aspect of the present invention there is provided the use of a removable patch comprising a hydrogel-precursor component, and a crosslinking
15 component, both as described hereinbefore, in the treatment of a surface, preferably by the sequential application of said components to said surface.

According to another aspect of the present invention there
20 is provided the use of a removable patch comprising a hydrogel-precursor component, and a crosslinking component, both as described hereinbefore, in the removal of a stain, or part of a stain, from a surface, or a reduction in the amount of said stain, preferably by the
25 sequential application of said components to said surface.

According to another aspect of the present invention there is provided a kit comprising a hydrogel precursor component, and a crosslinking component, both as described
30 hereinbefore.

According to another aspect of the present invention there is provided an applicator means comprising a plurality of

separate compartments and wherein each compartment contains at least either a hydrogel-precursor component, and a crosslinking component, both as hereinbefore described, such that said components are kept apart, or
5 substantially kept apart, as and until the components are sequentially applied to a surface to form a removable patch.

According to yet another aspect of the present invention
10 there is provided a method for the treatment of a surface, particularly the treatment of a soft surface, such as for example a textile, comprising the steps of the sequential application to said surface of at least two components as hereinbefore described to form a removable patch on said
15 surface.

According to another aspect of the present invention there is provided a method for the treatment of a surface, particularly the treatment of a soft surface, such as for
20 example a textile, comprising the steps of the sequential application to said surface of at least two components as hereinbefore described to form a patch on said surface.

Finally, according to an aspect of the present invention
25 there is provided the use of a kit comprising a hydrogel-precursor component, and a crosslinking component, both as described hereinbefore, in the treatment of a surface, preferably the removal of a stain, or part of a stain, from a surface, or a reduction in the amount of said
30 stain, preferably by the sequential application of said components to said surface.

By "compartments", we simply mean a region or container where the particular component is kept until use.

For the avoidance of any doubt, each and every feature described hereinbefore in relation to the first aspect of the present invention is equally applicable to any or all of the other aspects of the present invention, unless such features are incompatible with the particular aspect or mutually exclusive.

10

The sequential application of the components to the surface can be carried out by any convenient means, for example, by roll-on, spraying (e.g. from an aerosol or pump dispenser), brushing, painting, pouring, rubbing, squeezing etc., but sequential application by spraying or squeezing from a compartment is preferred. Examples of suitable applicator means include any multi-compartment device wherein the components are kept separate from each other as and until application by the user is desired. As such, the separator means can be any substantially non-porous structure. Applicator means should preferably be user-friendly and easily-portable, such as multi-compartment blister packs (with each component in a separate blister), or multi-headed or nibbed applicators (wherein each component is within a separate compartment within the body of the applicator). Moreover, the dispensing element is preferably designed to match the preferred mode of application for the particular component, i.e. brush-type application, spray nozzle, nib-like, roll-on applicator etc.

20
25
30

Preferably, the ratio of the total volume of crosslinking component to the total volume of hydrogel-precursor

component employed in the method of the invention is from 1:10 to 10 to 1, more preferably from 1:5 to 5:1, even more preferably from 1:3 to 3:1 and most preferably from 1:2 to 2:1.

5

When the applicator means is to sequentially apply two components, the applicator comprises two separate compartments. However, when the applicator means is to sequentially apply more than two components, either an
10 equivalent number of separate compartments can be provided or, alternatively, an equivalent number of separate compartments can be provided equal to the number of different components.

15 Preferably, the compartments of the applicator contain pre-measured amounts of component to ensure application of the preferred amounts of components. Moreover, compartments may be numbered, or otherwise labelled, to ensure the correct order of sequential application of
20 components.

The present invention will now be further illustrated by means of the following non-limiting Examples.

25 Example 1
Stain Removal Tests

Pre-stained cotton swatches were obtained from Wfk-Cleaning Technology Research Institute, Krefeld, Germany.
30 The swatches were pre-stained with either coffee or red wine.

A hydrogel-precursor component was formed by dispersing Protanal™LF20™ alginate (3 wt%) in glycerol (8 wt%). De-ionized water was then added (in an amount to ensure the wt% figures given herein for the component), followed by sodium lauroyl sarcosinate (4 wt%), and Dequest 2066™ sequestrant (0.75 wt%). This was all performed at room temperature and atmospheric pressure. A crosslinking component (component 1) was formed by mixing $\text{CaCl}_2 \cdot 2\text{H}_2\text{O}$ (1.1 wt%) in de-ionized water at room temperature and atmospheric pressure.

All wt% figures given above are based on the total weight of the particular respective crosslinking or hydrogel-precursor component.

15

The components were then applied to the pre-stained swatches in the following sequence: component 1, followed by component 2, followed by component 1. Component 1 was applied via spraying; component 2 was applied by squeezing from a tube or bottle. Approximately 20 secs was left between the application of each component before the next was added. The patch was then left for 10 mins, after which time the presence of the sodium lauroyl sarcosinate surfactant ensured that the patch that had formed appeared a white colour. The patch was then removed manually by peeling.

Table 1 below shows the results of the stain-removal tests, with the removal score assessed by an expert panel being on a scale of 0-10, where 0 represents no visible removal of stain and 10 represents complete removal of stain.

Table 1

<u>Stain on swatch</u>	<u>Removal Score</u>
Coffee	7
Red Wine	6

Moreover, no unpleasant odour was emitted during the test from the patch, swatch or stain, and the swatch remained colour-fast even after patch removal.

Clearly, the method of the present invention was successful in removing/reducing a selection of common stains.

By way of comparison, addition of component 2 alone, i.e. without component 1, led to no patch formation, nor any stain removal. Similar results were found by adding only component 1 to the stain.

Example 2

The following composition was prepared as hydrogel-precursor component.

Hydrogel Component:

Protanal™ LF20™	3%
Glycerol	8%
Dequest™ 2066	0.75%
Sodium Lauryl Sulphate	4%
Hydrogen Peroxide	2%
pH adjusted to 8 with NaOH solution	
Balance to 100% with DI water	

The crosslinking component was an aqueous solution of 15% w/w $\text{CaCl}_2 \cdot 2\text{H}_2\text{O}$.

Stain removal tests were carried out as detailed for example 1, but in this case the stains had been freshly made on cotton 400 swatches ex Westlairs. In this example, the evaluation scale was as follows:

- 1 Stain completely removed
- 2 Halo of stain is visible
- 3 Stain clearly visible
- 10 4 Stain strongly visible
- 5 As reference

The results were as follows:

15	Red Wine	2.2
	Coffee	1.9
	Mixed red fruit juice	2.1
	Blue ink	3.0
	Tomato	3.8
20	Tea	2.2

CLAIMS

1. A method for the treatment of a surface comprising the sequential application to the surface of a hydrogel-precursor component and a crosslinking component in either order to form a removable hydrogel patch on said surface, and the removal of the patch once the removable hydrogel patch has formed or substantially formed thereon.
2. A method as claimed in claim 1 wherein the surface is a soft surface.
3. A method as claimed in claim 2 wherein the soft surface is selected from the list consisting of textiles, clothing, carpets, curtains, and upholstery.
4. A method as claimed in claim 1 wherein the surface is a hard surface.
5. A method as claimed in any preceding claim wherein the removal is achieved by peeling said patch from the surface.
6. A method as claimed in any of claims 1 to 3 wherein the removal is via a washing process.
7. A method according to any preceding claim wherein the crosslinking component is applied to the surface prior to the application of the hydrogel-precursor component.
8. A method according to claim 7 wherein a second application of the crosslinking component is made after the application of the hydrogel-precursor component.

9. A method as claimed in any preceding claim wherein the crosslinking component comprises M^{2+} ions, where M is
5 a Group IIA element or any other metallic element capable of exhibiting a +2 oxidation state, and the hydrogel-precursor component comprises an alginate.

10. A method as claimed in claim 9 wherein the M^{2+} ions
10 are Ca^{2+} ions.

11. A method as claimed in claim 9 or 10 wherein the alginate is a sodium alginate.

15 12. A method as claimed in any of claims 1 to 11 wherein said hydrogel-precursor is present in the range 0.25 to 5 wt% of the weight of the component containing said hydrogel-precursor.

20 13. A method according to any one of claims 9 to 12 wherein the M^{2+} ions are present as 0.03 to 5% by weight of the crosslinking component.

14. A method as claimed in any preceding claim wherein
25 at least one of the crosslinking or hydrogel-precursor components further comprises one or more of the following: a bleach, an enzyme and a surfactant.

15. Use of a removable patch comprising crosslinking
30 and hydrogel precursor components as defined in any of claims 1 to 14, in the removal of a stain from a surface, wherein said patch is formed by the sequential application of the components to the surface.

16. A kit comprising a hydrogel-precursor-containing component, and a crosslinking component, both as defined
5 in any of claims 1 to 14.

17. Use of a kit comprising a hydrogel-precursor-containing component, and crosslinking component, as defined in any of claims 1 to 14, in the treatment of a
10 surface by the sequential application of the components to the surface.

18. An applicator means comprising a plurality of separate compartments and wherein each compartment
15 contains at least either a hydrogel-precursor component, or a crosslinking component, both as defined in any of claims 1 to 14, such that said components are kept apart as and until the components are sequentially applied to a surface to form a removable hydrogel patch.

20

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB2005/000428

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 C11D3/22 C11D3/37

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 C11D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98/08601 A (UNIVLEVER PLC; UNILEVER N.V) 5 March 1998 (1998-03-05) claims; examples	16, 18
X	----- DATABASE WPI Section Ch, Week 199704 Derwent Publications Ltd., London, GB; Class A96, AN 1997-038024 XP002328201 & JP 08 295706 A (WHITE LILY KK) 12 November 1996 (1996-11-12) abstract	16
X	----- WO 96/13285 A (INNOVATIVE TECHNOLOGIES LIMITED) 9 May 1996 (1996-05-09) claim 16; examples	16
	----- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the International filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

13 May 2005

Date of mailing of the international search report

30/05/2005

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Pfannenstein, H

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB2005/000428

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96/07711 A (MULTIFORM DESICCANTS, INCORPORATED) 14 March 1996 (1996-03-14) page 13; claims; examples -----	16, 17
A	WO 02/102957 A (RECKITT BENCKISER LIMITED) 27 December 2002 (2002-12-27) cited in the application claims; examples -----	1, 15
A	EP 0 257 966 A (RECKITT AND COLMAN PRODUCTS LIMITED) 2 March 1988 (1988-03-02) claims; examples -----	1, 15
A	WO 01/54836 A (HENKEL CORPORATION) 2 August 2001 (2001-08-02) claims; examples -----	1, 15

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB2005/000428

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9808601	A	05-03-1998	US 5726138 A US 5759969 A AU 714022 B2 AU 4300697 A BR 9711968 A CA 2265465 A1 CN 1234751 A CZ 9900672 A3 WO 9808601 A1 EP 0920353 A1 JP 2001502365 T KR 2000035850 A PL 331836 A1 US 6066613 A	10-03-1998 02-06-1998 16-12-1999 19-03-1998 24-08-1999 05-03-1998 10-11-1999 17-11-1999 05-03-1998 09-06-1999 20-02-2001 26-06-2000 02-08-1999 23-05-2000
JP 8295706	A	12-11-1996	NONE	
WO 9613285	A	09-05-1996	AU 3750495 A DE 69533227 D1 EP 0788380 A1 ES 2221931 T3 WO 9613285 A1 GB 2308846 A ,B JP 10507942 T US 6372248 B1	23-05-1996 05-08-2004 13-08-1997 16-01-2005 09-05-1996 09-07-1997 04-08-1998 16-04-2002
WO 9607711	A	14-03-1996	US 5641425 A AT 194163 T AU 688971 B2 AU 3500195 A BR 9509003 A CA 2199388 A1 DE 69517692 D1 DK 779915 T3 EP 0779915 A1 JP 3545765 B2 JP 10508327 T NZ 292735 A US 6156231 A WO 9607711 A1 US 5746937 A	24-06-1997 15-07-2000 19-03-1998 27-03-1996 25-11-1997 14-03-1996 03-08-2000 28-08-2000 25-06-1997 21-07-2004 18-08-1998 27-04-1998 05-12-2000 14-03-1996 05-05-1998
WO 02102957	A	27-12-2002	GB 2376472 A EP 1404804 A1 WO 02102957 A1 US 2004154107 A1	18-12-2002 07-04-2004 27-12-2002 12-08-2004
EP 0257966	A	02-03-1988	AU 7735787 A BR 8704393 A DK 447487 A EP 0257966 A2 FI 873738 A GB 2194972 A JP 63066383 A NO 873619 A PT 85613 A US 4802997 A ZA 8706346 A	03-03-1988 19-04-1988 29-02-1988 02-03-1988 29-02-1988 23-03-1988 25-03-1988 29-02-1988 01-09-1987 07-02-1989 27-04-1988

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB2005/000428

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0257966 A		ZW 15987 A1	18-11-1987
WO 0154836 A	02-08-2001	AU 3308801 A	07-08-2001
		WO 0154836 A1	02-08-2001